


HK...RS 系列



select	Inquiry	Bearing No.	Boundary dimensions □mm□			Basic load ratings(kN)		Limiting speed(rpm Mass) Oil Kg
			Fw	D	C	Dynamic(Cr)	Static(Cor)	
HK0810-RS	8	12	10	2250	2100	19000	2.9	
HK09X13X12-RS	8	13	12	3800	4300	19000	4	
HK1012-RS	10	14	12	4100	5000	19000	4.2	
HK1214-RS	12	18	14	6100	7000	15000	10.7	
HK13X19X12-RS	13	19	12	6800	7580	12000	8.9	
HK1414-RS	14	20	14	6100	7500	13000	12	
HK1514-RS	15	21	14	6800	8800	11000	12.6	
HK1518-RS	15	21	18	9500	11400	10000	16	
HK1614-RS	16	22	14	7200	9200	10000	15.1	
HK17X25X14-RS	17	25	14	8000	9800	10000	17.7	
HK17X25X15.5-RS	17	25	15.5	9320	10400	13000	20	
HK17X25X20-RS	17	25	20	11600	13200	13000	26.2	
HK1814-RS	18	24	14	7800	9900	13000	15.1	
HK2012-RS	20	26	12	9500	11900	9200	11.7	
HK2018-RS	20	26	18	12700	20100	8200	21.4	
HK20X29X18-RS	20	29	18	8700	9980	7800	28.8	
HK2212-RS	22	28	12	8310	10000	9000	14	
HK2214-RS	22	28	14	9000	12400	7800	18.3	
HK2218-RS	22	28	18	10400	20100	7800	23.5	
HK2518-RS	25	32	18	13600	20000	6900	31	
HK3018-RS	30	37	18	16200	26000	5300	36.6	

HK...RS 系列

HK3518-RS	35	42	18	16700	30500	4900	37.4
HK4018-RS	40	47	18	19000	30500	4200	47.3
HK4518-RS	45	52	18	20300	41000	3800	54.2
HK5022-RS	50	58	24	30000	61000	3200	77.2