



select	Inquiry	Bearing No.	Boundary dimensions □mm□			Basic load ratings(kN)		Limiting speed(rpm Mass) Oil	Kg
			Fw	D	C	Dynamic(Cr)	Static(Cor)		
RNA6918	105	125	63	174000	38000	4000	1250		
RNA6919	110	130	63	196000	400000	3870	1325		
RNA6917	100	120	63	161000	337000	4600	1112		
RNA6916	90	110	54	130500	280600	4927	978		
RNA6915	85	105	54	128000	272000	5130	923		
RNA6914	80	100	54	121000	263000	5130	815		
RNA6913	72	90	45	87600	194500	6100	571		
RNA6912	68	85	45	88500	186000	6100	436		
RNA6911	63	80	45	82560	172000	6340	430		
RNA6909	52	68	40	61500	123500	7625	308		
RNA6908	48	62	40	64000	112000	8120	238		
RNA6907	42	55	36	26000	60500	8710	160		
RNA69/32	40	52	36	25500	68500	881	147		
RNA6906	35	47	30	35000	67000	12000	116		
RNA69/28	32	45	30	39500	61300	13100	125		
RNA6905	30	42	30	26300	31750	12066	106.5		
RNA6904	25	37	30	26000	43000	14060	97.7		
RNA6903	22	30	23	14000	19900	16300	39.8		
RNA6902	20	28	23	13000	25000	12716	35.4		
RNA6901	16	24	22	14000	18600	15522	28.7		

RNA69 系列

RNA6900	14	22	22	8281	11612	18322	29.1	
---------	----	----	----	------	-------	-------	------	--