



select	Inquiry	型号	外形尺寸			基本额定载荷		极限速度 (X1000 RPM)		重 油 量(Kg)
			d	D	B	Cr(N)	Cor(N)	脂		
63800	10mm	19mm	7mm	1716	840	37	43	7.4		
63800 2rs	10mm	19mm	7mm	1716	840	37	43	7.4		
63800zz	10mm	19mm	7mm	1716	840	37	43	7.4		
6700	10mm	15mm	3mm	855	435	15	17	1.4		
6700 2rs	10mm	15mm	4mm	855	435	15	17	1.9		
6700zz	10mm	15mm	4mm	855	435	15	17	1.9		
6800	10mm	19mm	5mm	1716	840	37	43	5.6		
6800 2rs	10mm	19mm	5mm	1716	840	37	43	5.6		
6800zz	10mm	19mm	5mm	1716	840	37	43	5.6		
6900	10mm	22mm	6mm	2695	1273	34	41	10		
6900 2rs	10mm	22mm	6mm	2695	1275	34	41	10		
6900zz	10mm	22mm	6mm	2695	1273	34	41	10		
63801	12mm	21mm	7mm	1915	1041	33	39	8.5		
63801 2rs	12mm	21mm	7mm	1915	1041	33	39	8.5		
63801zz	12mm	21mm	7mm	1915	1041	33	39	8.5		
6701	12mm	18mm	4mm	926	530	13	15	3.1		
6701 2rs	12mm	18mm	4mm	926	530	13	15	3.1		
6701zz	12mm	18mm	4mm	926	530	13	15	3.1		
6801	12mm	21mm	5mm	1915	1041	33	39	6.5		
6801 2rs	12mm	21mm	5mm	1915	1041	33	39	6.5		
6801zz	12mm	21mm	5mm	1915	1041	33	39	6.5		

公制系列

6901	12mm	24mm	6mm	2886	1466	31	36	12
6901 2rs	12mm	24mm	6mm	2886	1466	31	36	12
6901zz	12mm	24mm	6mm	2886	1466	31	36	12
63802	15mm	24mm	7mm	2073	1253	28	33	10
63802 2rs	15mm	24mm	7mm	2073	1253	28	33	10
63802zz	15mm	24mm	7mm	2073	1253	28	33	10
6702	15mm	21mm	4mm	927	582	11	13	3.6
6702 2rs	15mm	21mm	4mm	937	582	11	13	3.6
6702zz	15mm	21mm	4mm	937	582	11	13	3.6